

Code ERC60S – 60cm Stainless Steel Canopy



3 SPEED MOTOR

This range hood provides the option of 3 different speed levels ensuring you have the option to use your range hood at a low, medium or high level of operation.

HIGH EXTRACTION CAPACITY

The extraction capacity of 700m³/hr provides strength and power to this stylish range hood.

SAFETY THERMAL OVERLOAD SWITCH

To ensure peace of mind the overload switch provides by automatically switching off if a fire occurs and thereby prevents the fire being sucked up into the ceiling.

FUNCTIONS

- + 3 speed motor
- + 700m³/hr extraction capacity
- + Stainless Steel
- + Dishwasher safe cassette filters
- + Push button front controls
- + 150mm air flow outlet

WARRANTY: 2 YEARS

DISHWASHER SAFE CASSETTE FILTERS

For easy cleaning, the cassette filters can be placed in a dishwasher and can easily be removed re-connected from the range hood.

TIPS FOR BETTER USE

- Leave your range hood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- It is recommended the range hood be installed between 650mm and 750mm above the cook top
- It is also recommended that fumes from the range hood be ducted out into the atmosphere.
- Turn off the range hood before attempting to clean
- Installation must be through qualified technician.**

OPTIONAL ACCESORIES

CARBON FILTERS

Required when recirculating
CF160 – Carbon Filters to suit ERC60S

RANGEHOOD VENTILATION KITS – SUPUR-FLEX

- RFK150W – range hood-venting kit - wall
- RFK150E – range hood-venting kit – under eave
- RFK150T – range hood-venting kit – roof cowl

RANGEHOOD VENTILATION KITS – SEMI-RIGID

- RHK150W – range hood-venting kit - wall
- RHK150E – range hood-venting kit – under eave
- RHK150T – range hood-venting kit – roof cowl

PRODUCT DIMENSIONS

