

Code ESL6002S – 60cm Slide out Rangehood



3 SPEED MOTOR

This rangehood provides the option of 3 different speed levels ensuring you have the option to use your range hood at a low, medium or high level of operation.

HIGH EXTRACTION CAPACITY

The extraction capacity of 440m³/hr provides strength and power to this stylish rangehood.

DISHWASHER SAFE CASSETTE FILTERS

The cassette filters can be placed in a dishwasher for easy cleaning and can easily be removed re-connected from the range hood.

DECIBEL RATING

Low Speed – 52db
 Medium Speed – 55db
 High Speed – 60db

FEATURES

- + Stainless steel Front Fascia
- + Integrated front panel
- + 3 speed motor
- + 440m³/hr extraction capacity
- + Dishwasher safe cassette filters
- + Non-visible controls system
- + New smooth railing system
- + Automatic light function

TIPS FOR BETTER USE

- To remove all odors, steam etc. leave your range hood on for 15 minutes after the cooking of the food
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- It is recommended the range hood be installed between 650mm and 750mm above the cook top
- It is also recommended that fumes from the range hood be ducted out into the atmosphere.
- To ensure safe and effective cleaning turn off the range hood before attempting to clean
- **Installation must be through qualified technician.**

OPTIONAL ACCESSORIES

RANGEHOOD VENTILATION KITS

- RHKE65 – Wall – Eave vent kit
- RHKMR65 – Universal metal roof kit, includes flashing
- RHKTR65 – Universal tile roof kit, includes flashing

OPTIONAL RANGEHOOD ACCESSORIES

- Product Code: CF110 carbon filter (Requires x2)
- Product Code: EFLUE Galv. Flue 125mm x 1200mm

ELECTRICAL REQUIREMENT:

Rangehood is supplied with 10amp cord & plug.

PRODUCT DIMENSIONS

